





Flap heightmm	Flap widthmm									
	300	400	500	600	700	800	900	1000	1100	1200
300	1.4	1.9	2.4	2.8	3.3	3.8	4.2	4.7	5.2	5.6
350	1.6	2.1	2.7	3.2	3.7	4.3	4.8	5.3	5.9	6.4
400	1.8	2.4	3.0	3.6	4.2	4.8	5.3	5.9	6.5	7.1
450	2.0	2.6	3.3	3.9	4.6	5.2	5.9	6.6	7.2	7.9
500	2.2	2.9	3.6	4.3	5.0	5.7	6.5	7.2	7.9	8.6
550	2.3	3.1	3.9	4.7	5.5	6.2	7.0	7.8	8.6	9.4
600	2.5	3.4	4.2	5.0	5.9	6.7	7.6	8.4	9.3	10.1

Sample measurements table for calculating the flap weight in kg – without handlefor aluminium frames (19 x 20.6 mm) with 4 mm thick glass panel

Flap heightmm	Flap widthmm									
	300	400	500	600	700	800	900	1000	1100	1200
300	1.1	1.4	1.8	2.1	2.4	2.7	3.0	3.4	3.7	4.0
350	1.3	1.7	2.0	2.4	2.8	3.1	3.5	3.9	4.2	4.6
400	1.4	1.9	2.3	2.7	3.1	3.5	4.0	4.4	4.8	5.2
450	1.6	2.1	2.5	3.0	3.5	4.0	4.4	4.9	5.4	5.8
500	1.8	2.3	2.8	3.3	3.8	4.4	4.9	5.4	5.9	6.4
550	1.9	2.5	3.1	3.6	4.2	4.8	5.3	5.9	6.5	7.1
600	2.1	2.7	3.3	3.9	4.6	5.2	5.8	6.4	7.0	7.7

 Catalog links available.
Please select an Item.

More Information

-  [Send e-mail inquiry](#)
-  [Compare](#)
-  [Print](#)



365.75.729 FLAP STAY ST.NIP.PL.WH.275MM
White, length: 275 mm (10 13/16")

Product details

C	Determine by trial mounting mm
Adjustment	To adjust braking action, loosen or tighten screw on stay, as needed
Mounting	Screw-mounted
Material	Steel housing: Plastic
Finish	Nickel-plated Housing: White
Note	<ul style="list-style-type: none"> ■ Keep brake piston rod free of oil, grease and other contaminants at all times. ■ Reversible: can be installed left or right, configured for right hand installation.



Optional accessories



Zinc alloy, for panel thickness from 18 mm



Flap Hinge, 3-Way Adjustable and Detachable, Zinc 16 mm

 Log on

 Apps

E-mail: sales@hafeleamericas.com

Phone: 800.423.3531

 Print Page

