

### ■ Features:

- Constant voltage design
- European AC input range
- Protections: Short circuit / Over current
- Cooling by free air convection
- Isolation class II
- Class 2 power unit
- Fully encapsulated with IP67 level [5]



(for 12V, 24V)



Model	Power	Voltage	Current	Protection	Safety & EMC	Working temperature	Dimensions (L×W×H)
GPV-12-18	18 W	12 V	1,5 A			-30°C ÷ 70°C	129.5 x 25 x 21mm (L x W x H)
GPV-12-20	24 W	12 V	2 A			-20°C ÷ 70°C	140 x 32 x 25mm (L x W x H)
GPV-12-35e	36 W	12 V	3 A			-20°C ÷ 70°C	140 x 32 x 25mm (L x W x H)
GPV-12-35	36 W	12 V	3 A	Short circuit	EN 55015, EN 61347-2-13, EN 61347-1 IP67 Class C	-20°C ÷ 70°C	148 x 32 x 28mm (L x W x H)
GPV-12-50	48 W	12 V	4 A	Over current		-20°C ÷ 70°C	148 x 40 x 34mm (L x W x H)
GPV-12-60e	60 W	12 V	5 A	Cooling by free air convection		-20°C ÷ 70°C	148 x 32 x 28mm (L x W x H)
GPV-12-60	60 W	12 V	5 A			-30°C ÷ 70°C	162 x 42 x 33mm (L x W x H)
GPV-12-75	75 W	12 V	6 A			-30°C ÷ 70°C	162 x 42 x 33mm (L x W x H)
GPV-12-100	100 W	12 V	8,3 A			-30°C ÷ 70°C	187 x 52x 37 mm (L x W x H)
GPV-12-150	120 W	12 V	10 A			-20°C ÷ 70°C	203 x 70 x 45mm (L x W x H)
GPV-12-200	199 W	12 V	16 A			-30°C ÷ 70°C	205 x 70 x 45mm (L x W x H)